

Productivity
Simplified

DP 125i™ Digital Mailing

Designed with flexibility in mind, the **DP 125i™**, powered by Secap's IntelliLink technology represents the ultimate answer to the mailing needs of busy businesses. The latest digital technology makes processing mail quiet and efficient - the perfect office companion.



As seen on TV

 **NORTHERN**
SERVICES

No compromise

How will your business benefit?

Future-proof mailing - IntelliLink connects Secap's DP125i to a secure server, via the Internet, enabling services such as postal tariff changes, software updates and advertising slogans to be downloaded quickly and effortlessly.

Correct value postage - every letter, every time - The DP125i incorporates a 2.5kg integral weighing platform, freeing up desk space and guaranteeing that each letter or package bears the correct postage value.

Fast, accurate postage re-crediting - Replenish your meter 24 hours a day with simple one-touch refills via **Postage by Phone** - quick, secure and hassle-free.

Easy to use - All controls are fully integrated on one clear control panel with user-friendly instructions to guide the operator through each stage of processing mail.

Streamlined processing - Efficiently frank and seal mail pieces up to 9.5mm thick, whilst larger mail is quickly processed with self adhesive tape strips. Mailing couldn't be simpler with up to 5 presets for your most commonly used jobs.

Monitor postal spend - Control postage costs with tracking and reporting for up to 25 named departmental or client accounts.

Strengthen your brand - Enhance standard envelopes into eye-catching branded mail pieces with tailor made customised logos.

Track incoming mail - Date and time stamping incoming post mail is handled efficiently.

DP 125i™ technical specifications

Physical dimensions

Length	345mm
Depth	400mm
Height	230mm
Weight	6.8kg

Speed

Up to 30 letters per minute

Material sizes

Minimum material size	76mm x 127mm
Maximum material size	330mm x 381mm
Material thickness	9.5mm (max) to 0.18mm (min)
Envelope flap depth for sealing	76mm (max) to 22mm (min)

Electrical

100-240 V, 50/60 Hz, 3A

Noise

55dB

Connectivity requirements

Connects to a standard analog phone line

Operating features

- Slogan and town circle downloaded (by modem)
- 2.5kg integrated weighing platform
- Auto-dating
- Water level indicator
- Seal only/no seal modes
- Low postage warning
- High value protection
- Original value resetting
- Low ink warning
- Password security
- PC Interface
- 5 job presets
- Up to 25 accounts



10 Albion Way, Kelvin Industrial Estate,
East Kilbride, G75 OYN.

Tel: 01355 241333 Fax: 01355 241555
Email: sales@northernservices.co.uk
www.northernservices.co.uk



The DP 125i™ Digital Mailing System complies with the requirements of the Low Voltage Directive 73/23/EEC and the EMC